

## United States Patent and Trademark Office



UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/661,500	09/15/2003	Yuji Sato	117176	7403
25944 OLIFF & BER	7590 07/27/2007 RIDGE, PLC		EXAMINER	
P.O. BOX 19928 ALEXANDRIA, VA 22320			MILIA, MARK R	
ALEXANDRI	A, VA 22320		ART UNIT	PAPER NUMBER
			2625	
			MAIL DATE	DELIVERY MODE
			07/27/2007	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

	Application No.	Applicant(s)			
	10/661,500	SATO ET AL.			
Office Action Summary	Examiner	Art Unit			
	Mark R. Milia	2625			
The MAILING DATE of this communication appears on the cover sheet with the correspondence address Period for Reply					
A SHORTENED STATUTORY PERIOD FOR REPLY WHICHEVER IS LONGER, FROM THE MAILING D.  - Extensions of time may be available under the provisions of 37 CFR 1.1 after SIX (6) MONTHS from the mailing date of this communication.  - If NO period for reply is specified above, the maximum statutory period of Failure to reply within the set or extended period for reply will, by statute Any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	ATE OF THIS COMMUNICATIO 36(a). In no event, however, may a reply be tin will apply and will expire SIX (6) MONTHS from a cause the application to become ABANDONE.	N. mely filed n the mailing date of this communication. ED (35 U.S.C. § 133).			
Status					
1) Responsive to communication(s) filed on					
	– action is non-final.				
3) Since this application is in condition for allowar					
closed in accordance with the practice under Ex parte Quayle, 1935 C.D. 11, 453 O.G. 213.					
Disposition of Claims					
4)⊠ Claim(s) <u>1-18</u> is/are pending in the application.					
4a) Of the above claim(s) is/are withdrawn from consideration.					
5) Claim(s) is/are allowed.					
6)⊠ Claim(s) <u>1-18</u> is/are rejected.					
7) ☐ Claim(s) is/are objected to.					
8) Claim(s) are subject to restriction and/o	r election requirement.				
Application Papers	,				
9) The specification is objected to by the Examine	er.				
1.0)⊠ The drawing(s) filed on <u>15 September 2003</u> is/are: a)⊠ accepted or b)□ objected to by the Examiner.					
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).					
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).					
11)☐ The oath or declaration is objected to by the Ex	caminer. Note the attached Office	e Action or form PTO-152.			
Priority under 35 U.S.C. § 119	•				
12)⊠ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f). a)⊠ All b)□ Some * c)□ None of:					
1. Certified copies of the priority documents have been received.					
2. Certified copies of the priority documents have been received in Application No					
3. Copies of the certified copies of the priority documents have been received in this National Stage					
application from the International Bureau (PCT Rule 17.2(a)).					
* See the attached detailed Office action for a list of the certified copies not received.					
	•				
Attachment(s)					
Notice of References Cited (PTO-892)     Notice of Draftsperson's Patent Drawing Review (PTO-948)	4) Interview Summary Paper No(s)/Mail D				
3) Information Disclosure Statement(s) (PTO/SB/08)	5) Notice of Informal				
Paper No(s)/Mail Date	6) 🔲 Other:				

## **DETAILED ACTION**

## Claim Rejections - 35 USC § 101

1. 35 U.S.C. 101 reads as follows:

Whoever invents or discovers any new and useful process, machine, manufacture, or composition of matter, or any new and useful improvement thereof, may obtain a patent therefor, subject to the conditions and requirements of this title.

Claims 12-13 are rejected under 35 U.S.C. 101 because the claimed invention is directed to non-statutory subject matter. Claims 12-13 are drawn to functional descriptive material NOT claimed as residing on a computer readable medium.

Claims 12-13, while defining a program product, do not define a "computer-readable medium" and is thus non-statutory for that reasons. A program product can range from paper on which the program is written, to a program simply contemplated and memorized by a person. The examiner suggests amending the claim to recite "A computer-readable medium storing a program for...", or a similar amendment that embodies the program on "computer-readable medium" in order to make the claim statutory.

## Claim Rejections - 35 USC § 103

2. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

Art Unit: 2625

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

3. Claims 1, 6, 11, and 12 are rejected under 35 U.S.C. 103(a) as being unpatentable over U.S. Patent No. 7,143,141 to Morgan et al. in view of U.S. Patent No. 5,473,441 to Inuiya et al.

Regarding claim 1. Morgan discloses an image forming apparatus connectable to a WAN and a LAN and capable of conducting a bidirectional communication with each terminal in the WAN or the LAN (see column 3 lines 22-30), comprising: an image forming unit configured to form an image based on externally input data on a recording medium (see column 8 lines 17-25), a substitutional sending/receiving unit configured to send a request signal to a web server in the WAN upon reception of a request signal for web server from a LAN terminal in the LAN, and configured to receive content data sent from the web server as a response signal to the request signal (see Fig. 1, column 3 lines 15-18, 34-36, and 40-52, column 4 lines 13-20 and 39-46, and column 7 lines 18-60), a transfer unit configured to send the content data received by the substitutional sending/receiving unit to the LAN terminal that has sent the request signal for web server (see Figs. 1 and 5, column 3 lines 40-52, column 5 lines 23-27, and column 6 lines 38-54), an image formation requesting unit that causes the image forming unit to form an image based on the content data received by the substitutional sending/receiving unit by inputting the content data to the image forming unit (see column 8 lines 17-25), and a plurality of rendering modules that function to print or display retrieved content (see column 8 lines 6-16).

Art Unit: 2625

Morgan does not disclose expressly a switching unit configured to judge whether the content data received by the substitutional sending/receiving unit is suitable for capabilities of the LAN terminal, configured to cause the transfer unit to operate when judging that the content data is suitable for the capabilities of the LAN terminal, and configured to cause the image formation requesting unit to operate when judging that the content data is not suitable for the capabilities of the LAN terminal.

Inuiya discloses a video camera that can be switched between a movie mode selected when a video signal representing an image of the subject to be projected on a display device is recorded on a magnetic tape and a print (still) mode selected when a video signal representing an image of the subject to be printed using a printer is recorded on a magnetic tape (see Fig. 1 and column 5 line 64-column 6 line 7).

Regarding claim 11, Morgan discloses an image forming apparatus connectable to a WAN and a LAN and capable of conducting a bidirectional communication with each terminal in the WAN or the LAN, comprising: an image forming unit configured to form an image based on externally input data on a recording medium (see column 8 lines 17-25), and a communication control unit including a gateway unit and a wireless processing unit (see column 5 lines 3-11), wherein the gateway unit comprises: a substitutional sending/receiving unit configured to send a request signal to a web server in the WAN upon reception of a request signal for web server from a LAN terminal in the LAN, and configured to receive content data sent from the web server as a response signal to the request signal (see Fig. 1, column 3 lines 15-18, 34-36, and 40-52, column 4 lines 13-20 and 39-46, and column 7 lines 18-60), a transfer unit configured to send

Art Unit: 2625

the content data received by the substitutional sending/receiving unit to the LAN terminal that has sent the request signal for web server (see Figs. 1 and 5, column 3 lines 40-52, column 5 lines 23-27, and column 6 lines 38-54), an image formation requesting unit that causes the image forming unit to form an image based on the content data received by the substitutional sending/receiving unit by inputting the content data to the image forming unit (see column 8 lines 17-25), and a plurality of rendering modules that function to print or display retrieved content (see column 8 lines 6-16).

Morgan does not disclose expressly a switching unit configured to judge whether the content data received by the substitutional sending/receiving unit is suitable for capabilities of the LAN terminal, configured to cause the transfer unit to operate when judging that the content data is suitable for the capabilities of the LAN terminal, and configured to cause the image formation requesting unit to operate when judging that the content data is not suitable for the capabilities of the LAN terminal.

Inuiya discloses a video camera that can be switched between a movie mode selected when a video signal representing an image of the subject to be projected on a display device is recorded on a magnetic tape and a print (still) mode selected when a video signal representing an image of the subject to be printed using a printer is recorded on a magnetic tape (see Fig. 1 and column 5 line 64-column 6 line 7).

Regarding claim 12, Morgan discloses a program product for causing an image forming apparatus that is connectable to a WAN and a LAN, capable of conducting a bidirectional communication with each terminal in the WAN or the LAN and including an

Art Unit: 2625

image forming unit configured to form an image based on externally input data on a recording medium to execute procedures, comprising: a substitutional sending unit that sends a request signal to a web server in the WAN upon reception of a request signal for web server from a LAN terminal in the LAN (see Fig. 1, column 3 lines 15-18, 34-36, and 40-52, column 4 lines 13-20 and 39-46, and column 7 lines 18-60), a substitutional receiving unit that receives content data sent from the web server as a response signal to the request signal (see Fig. 1, column 3 lines 15-18, 34-36, and 40-52, column 4 lines 13-20 and 39-46, and column 7 lines 18-60), a transferring unit that transfers the content data received by the substitutional receiving unit to the LAN terminal that has sent the request signal for web server when judging that the content data is suitable for the capabilities of the LAN terminal (see Figs. 1 and 5, column 3 lines 40-52, column 5 lines 23-27, column 6 lines 38-54, and column 8 lines 6-16), and a plurality of rendering modules that function to print or display retrieved content (see column 8 lines 6-16).

Morgan does not disclose expressly a requesting unit that requests to form an image based on the content data by inputting the content data to the image forming unit when judging that the content data is not suitable for capabilities of the LAN terminal.

Inuiya discloses a video camera that can be switched between a movie mode selected when a video signal representing an image of the subject to be projected on a display device is recorded on a magnetic tape and a print (still) mode selected when a video signal representing an image of the subject to be printed using a printer is recorded on a magnetic tape (see Fig. 1 and column 5 line 64-column 6 line 7).

Art Unit: 2625

Morgan & Inuiya are combinable because they are from a similar field of endeavor, display or printing of received image content.

At the time of the invention, it would have been obvious to a person of ordinary skill in the art to combine a switch, similar to that described by Inuiya, with the system of Morgan to allow switching between rendering modules. Switches are well known and commonly used in the art and therefore it would have been obvious to have a switching unit between rendering modules, such as the display and print modules, to allow a user to obtain information even if a user does not have a display with a sufficient capability.

The suggestion/motivation for doing so would have been to allow a user to obtain information even if a user does not have a display with a sufficient capability.

Therefore, it would have been obvious to combine Inuiya with Morgan to obtain the invention as specified in claims 1, 11, and 12.

Regarding claim 6, Morgan further discloses wherein the image forming unit is configured to print an image based on externally input data on a recording sheet (see column 8 lines 6-16).

4. Claims 14 and 15 are rejected under 35 U.S.C. 103(a) as being unpatentable over Morgan and Inuiya in view of U.S. Patent Application Publication No. 2003/0053122 to Kinoshita.

Regarding claim 14, Morgan discloses an image forming apparatus connectable to a WAN and a LAN and capable of conducting a bidirectional communication with

Page 8

each terminal in the WAN or the LAN, comprising: an image forming unit configured to form an image based on externally input data on a recording medium (see column 8 lines 17-25), a substitutional sending/receiving unit configured to send a request signal to a web server in the WAN upon reception of a request signal for web server from a LAN terminal in the LAN, and configured to receive content data sent from the web server as a response signal to the request signal (see Fig. 1, column 3 lines 15-18, 34-36, and 40-52, column 4 lines 13-20 and 39-46, and column 7 lines 18-60), a transfer unit configured to send the content data received by the substitutional sending/receiving unit to the LAN terminal that has sent the request signal for web server (see Figs. 1 and 5, column 3 lines 40-52, column 5 lines 23-27, and column 6 lines 38-54), and a plurality of rendering modules that function to print or display retrieved content (see column 8 lines 6-16).

Morgan does not disclose expressly a data writing unit configured to write the content data received by the substitutional sending/receiving unit to a recording medium for data storage and a switching unit configured to judge whether the content data received by the substitutional sending/receiving unit is suitable for capabilities of the LAN terminal, configured to cause the transfer unit to operate when judging that the content data is suitable for the capabilities of the LAN terminal, and configured to cause the data writing unit to operate when judging that the content data is not suitable for the capabilities of the LAN terminal.

Art Unit: 2625

Kinoshita discloses a data writing unit configured to write the content data received by the substitutional sending/receiving unit to a recording medium for data storage (see paragraph 42).

Inuiya discloses a video camera that can be switched between a movie mode selected when a video signal representing an image of the subject to be projected on a display device is recorded on a magnetic tape and a print (still) mode selected when a video signal representing an image of the subject to be printed using a printer is recorded on a magnetic tape (see Fig. 1 and column 5 line 64-column 6 line 7).

Morgan, Inuiya, & Kinoshita are combinable because they are from a similar field of endeavor, display or printing of received image content.

At the time of the invention, it would have been obvious to a person of ordinary skill in the art to combine the data writing unit, as described by Kinoshita, and the switch, similar to that described by Inuiya, with the system of Morgan to allow switching between rendering modules. Switches are well known and commonly used in the art and therefore it would have been obvious to have a switching unit between rendering modules, such as the display and print modules, to allow a user to obtain information even if a user does not have a display with a sufficient capability.

The suggestion/motivation for doing so would have been to allow a user to obtain information even if a user does not have a display with a sufficient capability.

Therefore, it would have been obvious to combine Kinoshita with Morgan and Inuiya to obtain the invention as specified in claim 14.

Art Unit: 2625

Regarding claim 15, Kinoshita further discloses wherein the data writing unit sends the LAN terminal a message inquiring whether to write the content data received by the substitutional sending/receiving unit to the recording medium for data storage, and writes the content data to the recording medium for data storage when receiving an image formation instruction signal from the LAN terminal as a response to the message (see paragraph 42).

5. Claim 18 is rejected under 35 U.S.C. 103(a) as being unpatentable over Morgan and Inuiya in view of Japanese Patent Document No. 2001-236288 to Yamaguchi et al.

Morgan discloses an image forming apparatus connectable to a WAN and a LAN and capable of conducting a bidirectional communication with each terminal in the WAN or the LAN, comprising: an image forming unit configured to form an image based on externally input data on a recording medium (see column 8 lines 17-25), a substitutional sending/receiving unit configured to send a request signal to a web server in the WAN upon reception of a request signal for web server from a LAN terminal in the LAN, and configured to receive content data sent from the web server as a response signal to the request signal (see Fig. 1, column 3 lines 15-18, 34-36, and 40-52, column 4 lines 13-20 and 39-46, and column 7 lines 18-60), a transfer unit configured to send the content data received by the substitutional sending/receiving unit to the LAN terminal that has sent the request signal for web server (see Figs. 1 and 5, column 3 lines 40-52, column 5 lines 23-27, and column 6 lines 38-54), and a plurality of rendering modules that function to print or display retrieved content (see column 8 lines 6-16).

Art Unit: 2625

Morgan does not disclose expressly an announcing unit configured to announce that the content data received by the substitutional sending/receiving unit is not suitable for the capabilities of the LAN terminal and a switching unit configured to judge whether the content data received by the substitutional sending/receiving unit is suitable for capabilities of the LAN terminal, configured to cause the transfer unit to operate when judging that the content data is suitable for the capabilities of the LAN terminal, and configured to cause the announcing unit to operate when judging that the content data is not suitable for the capabilities of the LAN terminal.

Yamaguchi discloses an announcing unit configured to announce that the content data received by the substitutional sending/receiving unit is not suitable for the capabilities of the LAN terminal (see paragraphs 19 and 36-37).

Inuiya discloses a video camera that can be switched between a movie mode selected when a video signal representing an image of the subject to be projected on a display device is recorded on a magnetic tape and a print (still) mode selected when a video signal representing an image of the subject to be printed using a printer is recorded on a magnetic tape (see Fig. 1 and column 5 line 64-column 6 line 7).

Morgan, Inuiya, & Yamaguchi are combinable because they are from a similar field of endeavor, display or printing of received image content.

At the time of the invention, it would have been obvious to a person of ordinary skill in the art to combine the announcing unit, as described by Yamaguchi, and the switch, similar to that described by Inuiya, with the system of Morgan to allow switching between rendering modules. Switches are well known and commonly used in the art

and therefore it would have been obvious to have a switching unit between rendering modules, such as the display and print modules, to allow a user to obtain information even if a user does not have a display with a sufficient capability.

The suggestion/motivation for doing so would have been to allow a user to obtain information even if a user does not have a display with a sufficient capability.

Therefore, it would have been obvious to combine Yamaguchi with Morgan and Inuiya to obtain the invention as specified in claim 18.

6. Claims 2, 5, and 13 are rejected under 35 U.S.C. 103(a) as being unpatentable over Morgan and Inuiya as applied to claims 1 and 12 above, and further in view of Kinoshita.

Regarding claims 2 and 13, Morgan and Inuiya do not disclose expressly wherein the image formation requesting unit sends the LAN terminal a message inquiring whether to cause the image forming unit to form an image based on the content data received by the substitutional sending/receiving unit, and inputs the content data received by the substitutional sending/receiving unit to the image forming unit when receiving an image formation instruction signal from the LAN terminal as a response to the message.

Kinoshita discloses wherein the image formation requesting unit sends the LAN terminal a message inquiring whether to cause the image forming unit to form an image based on the content data received by the substitutional sending/receiving unit, and inputs the content data received by the substitutional sending/receiving unit to the

Art Unit: 2625

image forming unit when receiving an image formation instruction signal from the LAN terminal as a response to the message (see Figs. 5 and 6 and paragraphs 36-45).

Morgan, Inuiya, & Kinoshita are combinable because they are from a similar field of endeavor, display or printing of received image content.

At the time of the invention, it would have been obvious to a person of ordinary skill in the art to combine the image formation request and response to print content, as described by Kinoshita, with the system of Morgan and Inuiya.

The suggestion/motivation for doing so would have been to allow a user to obtain information even if a user does not have a display with a sufficient capability.

Therefore, it would have been obvious to combine Kinoshita with Morgan and Inuiya to obtain the invention as specified in claims 2 and 13.

Regarding claim 5, Morgan discloses a plurality of rendering modules that function to print or display retrieved content (see column 8 lines 6-16).

Morgan does not disclose expressly further comprising a data writing unit for writing the content data received by the substitutional sending/receiving unit to a recording medium for data storage, wherein the switching unit selectively causes the image formation requesting unit or the data writing unit to operate depending on a type of the content data when judging that the content data is not suitable for the capabilities of the LAN terminal that has sent the request signal for web server.

Art Unit: 2625

Kinoshita discloses a data writing unit for writing the content data received by the substitutional sending/receiving unit to a recording medium for data storage (see paragraph 42).

Inuiya discloses a video camera that can be switched between a movie mode selected when a video signal representing an image of the subject to be projected on a display device is recorded on a magnetic tape and a print (still) mode selected when a video signal representing an image of the subject to be printed using a printer is recorded on a magnetic tape (see Fig. 1 and column 5 line 64-column 6 line 7).

Morgan, Inuiya, & Kinoshita are combinable because they are from a similar field of endeavor, display or printing of received image content.

At the time of the invention, it would have been obvious to a person of ordinary skill in the art to combine the data writing unit, as described by Kinoshita, and the switch, similar to that described by Inuiya, with the system of Morgan to allow switching between rendering modules. Switches are well known and commonly used in the art and therefore it would have been obvious to have a switching unit between rendering modules, such as the display and print modules, to allow a user to obtain information even if a user does not have a display with a sufficient capability.

The suggestion/motivation for doing so would have been to allow a user to obtain information even if a user does not have a display with a sufficient capability.

Therefore, it would have been obvious to combine Kinoshita with Morgan and Inuiya to obtain the invention as specified in claim 5.

Art Unit: 2625

7. Claims 3-4 and 7-10 are rejected under 35 U.S.C. 103(a) as being unpatentable over Morgan and Inuiya as applied to claim 3 above, and further in view of Yamaguchi.

Regarding claim 3, Morgan discloses a plurality of rendering modules that function to print or display retrieved content (see column 8 lines 6-16).

Morgan does not disclose expressly a database for storing information relating to capabilities of each LAN terminal in the LAN, wherein the switching unit judges whether the content data received by the substitutional sending/receiving unit is suitable for the capabilities of the LAN terminal that has sent the request signal for web server on the basis of the information relating to capabilities of each LAN terminal stored in the database.

Yamaguchi discloses a database for storing information relating to capabilities of each LAN terminal in the LAN (see paragraphs 22, 35-37, and 39-40).

Inuiya discloses a video camera that can be switched between a movie mode selected when a video signal representing an image of the subject to be projected on a display device is recorded on a magnetic tape and a print (still) mode selected when a video signal representing an image of the subject to be printed using a printer is recorded on a magnetic tape (see Fig. 1 and column 5 line 64-column 6 line 7).

Regarding claim 7, Morgan and Inuiya do not disclose expressly wherein the switching unit judges that the content data received by the substitutional sending/receiving unit is suitable for capabilities of the LAN terminal when an image size of image data contained in the content data is within a screen size of a display unit of the LAN terminal.

Art Unit: 2625

Yamaguchi discloses wherein the switching unit judges that the content data received by the substitutional sending/receiving unit is suitable for capabilities of the LAN terminal when an image size of image data contained in the content data is within a screen size of a display unit of the LAN terminal (see paragraphs 35-37).

Regarding claim 8, Morgan and Inuiva do not disclose expressly wherein the switching unit judges that the content data received by the substitutional sending/receiving unit is suitable for capabilities of the LAN terminal when an image size of image data contained in the content data is within a screen size of a display unit of the LAN terminal.

Yamaguchi discloses wherein the switching unit judges that the content data received by the substitutional sending/receiving unit is suitable for capabilities of the LAN terminal when an image size of image data contained in the content data is within a screen size of a display unit of the LAN terminal (see paragraphs 35-37).

Regarding claim 9, Morgan and Inuiva do not disclose expressly wherein the switching unit judges that the content data received by the substitutional sending/receiving unit is suitable for capabilities of the LAN terminal when a display unit of the LAN terminal is capable of displaying image data that is color data or monochrome data and is contained in the content data.

Yamaguchi discloses wherein the switching unit judges that the content data received by the substitutional sending/receiving unit is suitable for capabilities of the LAN terminal when a display unit of the LAN terminal is capable of displaying image

data that is color data or monochrome data and is contained in the content data (see paragraphs 35-37).

Regarding claim 10, Morgan and Inuiya do not disclose expressly wherein the switching unit judges that the content data received by the substitutional sending/receiving unit is suitable for capabilities of the LAN terminal when a format of image data contained in the content data is extractable in the LAN terminal.

Yamaguchi discloses wherein the switching unit judges that the content data received by the substitutional sending/receiving unit is suitable for capabilities of the LAN terminal when a format of image data contained in the content data is extractable in the LAN terminal (see paragraphs 35-37).

Morgan, Inuiya, & Yamaguchi are combinable because they are from a similar field of endeavor, display or printing of received image content.

At the time of the invention, it would have been obvious to a person of ordinary skill in the art to combine the database for storing information relating to capabilities, as described by Yamaguchi, and the switch, similar to that described by Inuiya, with the system of Morgan to allow switching between rendering modules. Switches are well known and commonly used in the art and therefore it would have been obvious to have a switching unit between rendering modules, such as the display and print modules, to allow a user to obtain information even if a user does not have a display with a sufficient capability.

The suggestion/motivation for doing so would have been to allow a user to obtain information even if a user does not have a display with a sufficient capability.

Therefore, it would have been obvious to combine Yamaguchi with Morgan and Inuiya to obtain the invention as specified in claims 3 and 7-10.

Regarding claim 4, Yamaguchi further discloses a registering unit configured to judge whether information relating to the capabilities of the LAN terminal that has sent the request signal for web server is registered in the database, and configured to acquire information relating to the capabilities of the LAN terminal from the LAN terminal and register the information in the database when judging that the information is not registered in the database (see paragraphs 36-40).

8. Claims 16-17 are rejected under 35 U.S.C. 103(a) as being unpatentable over Morgan, Inuiya, and Kinoshita as applied to claim 14 above, and further in view of Yamaguchi.

Regarding claim 16, Morgan discloses a plurality of rendering modules that function to print or display retrieved content (see column 8 lines 6-16).

Morgan and Kinoshita do not disclose expressly a database for storing information relating to capabilities of each LAN terminal in the LAN, wherein the switching unit judges whether the content data received by the substitutional sending/receiving unit is suitable for the capabilities of the LAN terminal that has sent the request signal for web server on the basis of the information relating to capabilities of each LAN terminal stored in the database.

Art Unit: 2625

Yamaguchi discloses a database for storing information relating to capabilities of each LAN terminal in the LAN (see paragraphs 22, 35-37, and 39-40).

Inuiya discloses a video camera that can be switched between a movie mode selected when a video signal representing an image of the subject to be projected on a display device is recorded on a magnetic tape and a print (still) mode selected when a video signal representing an image of the subject to be printed using a printer is recorded on a magnetic tape (see Fig. 1 and column 5 line 64-column 6 line 7).

Morgan, Inuiya, Kinoshita & Yamaguchi are combinable because they are from a similar field of endeavor, display or printing of received image content.

At the time of the invention, it would have been obvious to a person of ordinary skill in the art to combine the database for storing information relating to capabilities, as described by Yamaguchi, with the system of Morgan, Inuiya, and Kinoshita.

The suggestion/motivation for doing so would have been to allow a user to obtain information even if a user does not have a display with a sufficient capability.\*

Therefore, it would have been obvious to combine Yamaguchi with Morgan and Inuiya to obtain the invention as specified in claim 16.

Regarding claim 17, Yamaguchi further discloses a registering unit configured to judge whether information relating to the capabilities of the LAN terminal that has sent the request signal for web server is registered in the database, and configured to acquire information relating to the capabilities of the LAN terminal from the LAN terminal

Art Unit: 2625

and register the information in the database when judging that the information is not

Page 20

registered in the database (see paragraphs 36-40).

Conclusion

Any inquiry concerning this communication or earlier communications from the

examiner should be directed to Mark R. Milia whose telephone number is (571) 272-

7408. The examiner can normally be reached M-F 8:00am-4:00pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's

supervisor, Twyler M. Lamb can be reached at (571) 272-7406. The fax number for the

organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the

Patent Application Information Retrieval (PAIR) system. Status information for

published applications may be obtained from either Private PAIR or Public PAIR.

Status information for unpublished applications is available through Private PAIR only.

For more information about the PAIR system, see http://pair-direct.uspto.gov. Should

you have questions on access to the Private PAIR system, contact the Electronic

Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a

USPTO Customer Service Representative or access to the automated information

system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

Mark R. Milia

Examiner

MI. I. W. J.

**MRM** 

SUPERVISORY PATENT EXAMINER